# **Test Report**

Report Number: 982711-1-ST



#### DANISH TECHNOLOGICAL INSTITUTE

Gregersensvej 1 DK-2630 Taastrup +45 72 20 20 00 info@teknologisk.dk www.teknologisk.dk

Page 1 of 3 Init.: JHA/LAHA Order no.: 982711 Encl.: 2

Assignor:	Siso A/S, Mileparken 11, DK-2740 Skovlunde
ltem:	06.11.220 Weka" Leg connector"
Sampling:	The assignor confirms having selected the product. The product was forwarded by the assignor and received at Danish Technological Institute on 30 June 2021.
Period:	The test took place from 30 June 2021 to 22 July 2021.
Method:	EN 15372:2016, Furniture - Strength, durability and safety - Requirements for non-domestic tables
	Test severity L3: Severe use: E.g. in night-clubs, police stations, transport terminals, hospital public areas, casinos, homes for the elderly, sports changing rooms, prisons, barracks.
	Additional information is given in enclosure B.
Test results:	Passed.
Test results:	Passed. The results are shown in enclosure A.
Test results: Terms:	
	The results are shown in enclosure A. This test was conducted accredited in accordance with international requirements (ISO/IEC 17025:2017) and in accordance with the General Terms and Conditions of Danish Technological Institute. The test results solely apply to the tested item. This test report may
Terms:	The results are shown in enclosure A. This test was conducted accredited in accordance with international requirements (ISO/IEC 17025:2017) and in accordance with the General Terms and Conditions of Danish Technological Institute. The test results solely apply to the tested item. This test report may be quoted in extract only if Danish Technological Institute has granted its written consent.







### Results

Test No.	Test	Test Method	Loading		Result		
5.1	General requirements						
5.2.1	Shear and squeeze points when setting up and folding						
5.2.2	Shear and squeeze points under influence of powered mechanisms						
5.2.3	Shear and squeeze points during use						
5.4.1-1	Horizontal static load test	EN 1730, 6.2	Test force, N Specified mass, kg Cycles	600 50 10	Passed		
5.4.1-2	Vertical static load on main surface	EN 1730, 6.3.1	Test force, N Cycles	1250 10	Passed		
5.4.1-3	Additional vertical static load test where the main surface has a length >1600 mm	EN 1730, 6.3.2	Test force, N Cycles	1000 10	Passed		
5.4.1-4	ertical static load on ancillary surface EN 1730, 6.3.3 Test force, N Cycles		300 10	N/A			
5.4.1-5	Horizontal durability test	EN 1730, 6.4.1 and 6.4.2	Test force, N Specified mass, kg Cycles	300 50 20000	Passed		
5.4.1-6	Vertical durability test for cantilever and tables with central column only	EN 1730, 6.5	Test force, N Cycles	300 20000	N/A		
5.4.1-7	/ertical impact test for glass tabletops EN 1730, 6.6.1 Drop height, mm and 6.6.2 Cycles		240 10	N/A			
5.4.1-8	Vertical impact test for all other tabletops	EN 1730, 6.6.1 and 6.6.3	Drop height, mm Cycles	180 10	Passed		
5.4.1-9	Drop test – This test is applicable for tables weighing more than 20 kg only	EN 1730, 6.9	Drop height, mm Cycles	50 6	Passed		
5.4.1-10	Stability under vertical load test	EN 1730, 7.2	Main surface Ancillary surface	400 200	Passed		
5.4.1-11	Stability for tables with extension elements	EN 1730, 7.3	Test force, N	200	N/A		
6	Information for use				N/A		
A.3.2	Durability of table with castors	EN 1730, 6.8	Specified load, N Cycles	20 2000	N/A		



### Information provided by the Danish Technological Institute

Photograph of the received sample



### Information required by EN 15372:2013

#### European Standards used:

EN 15372:2016 - Furniture – Strength, durability and safety – Requirements for non-domestic tables

EN 1730:2012 - Furniture - Tables - Test methods for the determination of stability, Strength and durability

#### Details of tested table:

Model:	06.11.220 Weka" Leg connector"			Туре:	Table		
Width:	800 mm	Length:	1800 mm	Height:	725 mm	Weight:	32.86 kg
Materials:	25 mm birch	plywood				-	

#### Details of defects observed before testing:

None.

## Details of any deviations from this standard:

None.

### Any variation from the specified temperature range:

None.

#### Test result:

See enclosure A.

#### Name and address of the test facility:

Danish Technological Institute, Gregersensvej, Taastrup 2630, Denmark

#### Date of test:

2021-06-30 to 2021-07-22